



# CORE AERATOR HD

20-70 HP (15-52 KW)  
cat. 1 & 2



## Heavy duty core aerators

- Hub spacing 6 1/2".
- Special high tensile steel shafts on the rotors.
- 2 bronze bushings per rotor.
- 3/16" formed steel support panels.
- All panels support rotors from all sides.

- 1 1/4" rotor support shaft.
- 3/8" formed Cat. 1 & 2 "A" frame.
- Machine equipped with spikes instead of spoons is available on request.
- 3 point linkage, Cat. 1 & 2.
- 8 spoons per hub.
- All flanges are welded to rotors.
- Flange thickness 3/16".
- 3/4" hardened steel spoons.
- Front or rear tractor mounting.
- 3 support stands.

### STANDARD



Eight spoons per flange



Choice of hollow spoons or solid spikes

MODEL		BCA-260	BCA-272
	HP	20-70	20-70
	in	60"	72"
	in	65"	78"
	lbs	444	549
	N°	5	6
	N°	10	12
	N°	80	96
	in	4 1/2"	4 1/2"
	in	19" x 21"	25" x 21"
	lbs	170 ea.	220 ea.

## OPTIONALS CORE AERATOR SD



- Steel weight sand tank, price per unit

**009-9731** BCA-048

**009-9732** BCA-060

**009-9733** BCA-072



- Unit with spikes instead of spoons (factory installed)

**SP048BCA** BCA-048

**SP060BCA** BCA-060

**SP072BCA** BCA-072

**FRTSDBC**

- Front mounted (factory installed)



## OPTIONALS CORE AERATOR HD



- Steel weight sand tank, price per unit

**009-9734** BCA-260

**009-9735** BCA-272



- Unit with spikes instead of spoons, (factory installed)

**SP260BCA** BCA-260

**SP272BCA** BCA-272

**FRTHDBC**

- Front mounted (factory installed)



## OPTIONALS SOIL PULVERIZERS SD



- 2nd rear roller assembly Ø 5"

**009-9887** BPL-048

**009-9636** BPL-060

**009-9637** BPL-072