

CORE AERATOR SD

20-50 HP (15-37 KW)
cat. 1



Standard duty core aerators

- Hub spacing 6 1/2".
- Special high tensile steel shafts on the rotors.
- 2 bronze bushings per rotor.
- 8 gauge formed steel support panels.
- All panels support rotors from all sides.
- 1 1/4" rotor support shaft.
- 3/8" formed Cat. 1 "A" frame.
- Machine equipped with spikes instead of spoons is available on request.
- 3 point linkage, Cat. 1.
- 6 spoons per hub.
- All flanges are welded to rotors.
- Flange thickness 3/16".
- 3 support stands.
- 3/4" hardened steel spoons.
- Front or rear tractor mounting.

MODEL		BCA-048	BCA-060	BCA-072
	HP	20-50	20-50	20-50
	in	48"	60"	72"
	in	54"	65"	78"
	lbs	284	357	401
	N°	4	5	6
	N°	8	10	12
	N°	48	60	72
	in	4 1/2"	4 1/2"	4 1/2"
	in	12" x 15"	19" x 15"	25" x 15"
	lbs	78 ea.	125 ea.	160 ea.

STANDARD



Front or rear tractor mounting



Both hub flanges are welded and equipped with two bronze bushings per rotor

OPTIONALS CORE AERATOR SD



- Steel weight sand tank, price per unit

009-9731 BCA-048

009-9732 BCA-060

009-9733 BCA-072



- Unit with spikes instead of spoons (factory installed)

SP048BCA BCA-048

SP060BCA BCA-060

SP072BCA BCA-072

FRTSDBC

- Front mounted (factory installed)



OPTIONALS CORE AERATOR HD



- Steel weight sand tank, price per unit

009-9734 BCA-260

009-9735 BCA-272



- Unit with spikes instead of spoons, (factory installed)

SP260BCA BCA-260

SP272BCA BCA-272

FRTHDBC

- Front mounted (factory installed)



OPTIONALS SOIL PULVERIZERS SD



- 2nd rear roller assembly Ø 5"

009-9887 BPL-048

009-9636 BPL-060

009-9637 BPL-072