



## CYCLONE C70

30-70 HP (22-52 KW)  
540 rpm - cat. 1















### Heavy duty rear discharge three spindle grooming mower

- Highly engineered & rugged gearbox with cooling fins.
- Cutting heights: from 1.3" to 5.3".
- Front & rear tractor mounting.
- 4 rubber swivel tires with bearings to guarantee a perfectly level cut.
- Stamped steel reinforced wheel arm attached by 8 bolts for maintaining a consistent cutting height.


- Floating 3 point linkage, cat. 1.
- Front antiscalping roller standard.
- 8 gauge reinforced mower deck.
- Three spindle rotors with free swinging blades per rotor.
- Spindle shafts greased from the top for easy service.
- Two heavy duty reinforced belts (CX).
- Heavy duty, one piece, balanced steel pulleys.
- Heavy duty shielded PTO shaft (1 3/8" ASAE cat. 4).
- Safety chain shield standard.
- Stamped steel wheel yokes.



MODEL		C70-090H	C70-110H	C70-090A	C70-110A
		HARD TIRES		AIR TIRES	
	HP	30-70	40-70	30-70	40-70
	in	90"	110"	90"	110"
	in	92"	112"	92"	112"
	lbs	1,237	1,390	1,137	1,290
	lbs	1,267	1,420	1,167	1,320
	rpm	1,750	1,562	1,750	1,562
	fpm	14,106	14,998	14,106	14,998
	N°	6	6	6	6
	in	1.3"-5.3"	1.3"-5.3"	1.3"-5.3"	1.3"-5.3"
	N°	2 CX	2 CX	2 CX	2 CX
	N°-in	4-12"x4"	4-12"x4"	4-13"x6.5"	4-13"x6.5"
	1 3/8"	ASAE cat. 4	ASAE cat. 4	ASAE cat. 4	ASAE cat. 4



## STANDARD



Reversible three point hitch for front or rear tractor mounting



Gearboxes manufactured by Befco



Stamped steel wheel arms attached by eight bolts



Choice of hard or air tires



Axial grease fittings for easy and accurate spindle lubrication



Chains provide safety from thrown objects



Standard front antiscalping roller



Rotor with free swinging blades

## OPTIONALS CYCLONE C50

- Mulching kit



**009-9184** C50-RD5

**009-9185** C50-RD6

**009-9186** C50-RD7

**009-9915**



- Front antiscalping roller  
(standard on C50-RD7 model)

**002-800**

- Quick hitch adapter



**FRTXXC50**



- Front mount C50  
(factory installed)

## OPTIONALS CYCLONE C70

**002-800**

- Quick hitch adapter



**FRTXXC70**



- Front mount C70  
(factory installed)

## OPTIONALS CYCLONE FLEX

**009-9817**

- Hydraulic unlocking system



- Mulching kit



**009-9556** 312-FLX

**009-9557** 315-FLX

**009-9558** 317-FLX

**009-9597**

- Floating hitch, additional



**009-9599**

- Roadway kit

