



## CYCLONE SUPER-FLEX

35-80 HP (26-60 KW)


540 rpm












### Pull type gang grooming mowers

- Extra heavy duty transport frame.
- Cutting heights: from 1" to 5".
- Pull type mower with high flotation transport tires (23"x10.5"x12").
- Single action hydraulic folding wing system for easy transport & storage.
- 3 front antiscalping rollers standard.
- Telescoping wings that allow for adjustable cutting width to increase or decrease mower overlap.
- Constant velocity driveline with slip clutch (1 3/8" ASAE cat. 6).
- Stamped steel reinforced wheel arm attached by 8 bolts for maintaining a consistent cutting height.
- Stamped steel wheel yokes.
- 8 gauge reinforced mower deck.



- Safety chain shield standard.
- Single unit driveline with shear pin safety.
- Remote safety locks for local transport & deck kick out attachments.
- Completely independent free floating mowing decks for a perfect cut on uneven terrain.
- Unique double pivot floating linkage.
- 12 rubber tires with bearings (4 per deck) to guarantee a perfectly level cut.
- Wide high flotation air tires 13"x6.5".
- Heavy duty, one piece, balanced steel pulleys.
- Two heavy duty reinforced belts per deck (SPBX).
- Single unit gearboxes with cooling fins.
- Spiral gears guarantee strength and quietness.



MODEL		412-SFL	415-SFL	417-SFL	420-SFL
	HP	35-80	40-80	45-80	50-80
	ft	12'	15'	17'	20'
	in	91"	97"	100"	114"
	in	74"	92"	103"	116"
	lbs	3,090	3,267	3,438	3,747
	N°	9	9	9	9
	in	1"-5"	1"-5"	1"-5"	1"-5"
	N°	6 SPBX	6 SPBX	6 SPBX	6 SPBX
	N°-in	12-13"x6.5"	12-13"x6.5"	12-13"x6.5"	12-13"x6.5"
	N°-ft	2-4' mowers & 1-5' mower	2-5' mowers & 1-6' mower	3-6' mowers	3-7' mowers
	1 3/8"	ASAE cat. 6 cv, slip clutch	ASAE cat. 6 cv, slip clutch	ASAE cat. 6 cv, slip clutch	ASAE cat. 6 cv, slip clutch



Heavy duty center-splitter gearbox

## STANDARD



Double pivot floating linkage for a perfect cut on uneven terrain



Telescopic wings that allow for adjustable cutting width to increase or decrease mower overlap



Gearboxes, manufactured by Befco, equipped with spiral gears to increase strength and quietness



Air tires 13"x6.5"



Hexagonal yokes on front tires of rear mower deck prevent slippage on slopes

## OPTIONALS CYCLONE SUPER FLEX

009-9817

- Hydraulic unlocking system



- Mulching kit



009-9556 412-SFL

009-9305 415-SFL

009-9306 417-SFL

009-9307 420-SFL

009-9597

- Front floating hitch, additional



009-9599

- Roadway kit



## OPTIONALS HURRICANE H40-S

009-9206

- Side skids



009-9560

- Overrunning clutch for driveline



- Rotor with dethatching blades (factory installed)

DBD48H40 H40-S48

DBD60H40 H40-S60

DBD72H40 H40-S72



- Rotor with reverse "Y" blades (factory installed)

YBD48H40 H40-S48

YBD60H40 H40-S60

YBD72H40 H40-S72



- Rotor with triangular paddle blades (factory installed)

TBD48H40 H40-S48

TBD60H40 H40-S60

TBD72H40 H40-S72



- Rotor with hammers (factory installed)

HBD48H40 H40-S48

HBD60H40 H40-S60


HBD72H40 H40-S72

009-9207

- Hydraulic cylinder for side shift



- Front steel deflectors



009-9208 H40-S48

009-9209 H40-S60

009-9210 H40-S72

RVRXXH40

- Reverse rotation (factory installed)



FRTXXH40

- Front mount H40 (factory installed)

