

GREEN-RITE GRT














25-70 HP (19-52 KW)
540 rpm - cat. 1



Overseeder-aerator & seeder-cultivator

- Special 2-¹³/₁₆" spacing on rotor for aerating with 3 knives per flange; 4 knives on model 282.
- 2" to 3" suggested working depth with aerator rotor, 7 ¹/₄" working depth with tiller rotor; 8 ³/₄" on on model 282.
- Seed covering/dethatching adjustable tickler tines.
- High precision metering seed cups made from a nylon/fiberglass composite.
- Parking stand.
- Ground drive system for seed hopper.
- Large capacity seed hopper with agitator.
- Heavy duty shielded PTO shaft with slip clutch safety (1 ³/₈" ASAE cat. 3 for models 250, 258 & 266, cat. 6 for model 282).
- Corrugated depth control roller made with low weight nylon/fiberglass roller rings.
- Double sided, extra thin profile razor blades reduce impact when aerating over existing turf (available on request).



MODEL		GRT-250	GRT-258	GRT-266	GRT-282
	HP	25-45	30-45	32-45	40-70
	in	50"	58"	66"	82"
	in	57"	66"	74"	89"
	lbs	910	998	1,170	1,500
	lbs	1,160	1,245	1,390	1,760
	cu.ft	4.60	5.30	6.00	7.60
	N°	7	8	9	11
	N°	15	18	21	26
	N°	43	52	61	104
	z	11-14	11-14	11-14	12-14
	rpm	231	231	231	221
	in	7 1/4"	7 1/4"	7 1/4"	8 3/4"
	1 3/8"	ASAE cat. 3 slip clutch	ASAE cat. 3 slip clutch	ASAE cat. 3 slip clutch	ASAE cat. 6 slip clutch

STANDARD



Aerator rotor with straight blades with 2-1/8" flange spacing



Corrugated roller with nylon/fiberglass rings to compact the ground for optimal seed germination



Precise seed metering cups



Seed calibration handle



Lift hooks easy loading and unloading



Tickler tines for partial or complete seed incorporation into the ground

OPTIONALS TILL-RITE T60

RVRXXT60

• Reverse rotation (factory installed)



OPTIONALS TILL-RITE T70

RVRXXT70

• Reverse rotation (factory installed)



009-9855

• Areator rotor T70-382



OPTIONALS GREEN-RITE GRT

009-9875

• Gauge wheels for all models



• Front roller



009-9648

GRT-250

009-9516

GRT-258

009-9563

GRT-266

009-9566

GRT-282

Note: units may utilize gauge wheels or front roller for depth control, but not both

• Tiller rotor



009-9649

GRT-250

009-9517

GRT-258

009-9564

GRT-266

009-9567

GRT-282

• Rear roller scraper



009-9189

GRT-250

009-9190

GRT-258

009-9191

GRT-266

009-9192

GRT-282

• Cast iron roller rings
(factory installed)



CSR50GRT

GRT-250

CSR58GRT

GRT-258

CSR66GRT

GRT-266

CSR82GRT

GRT-282

• Seed conveyor kit



009-9139

GRT-250

009-9140

GRT-258

009-9141

GRT-266

009-9142

GRT-282