

# REAR BLADE HD

30-80 HP (22-60 KW)  
cat. 1 & 2



## Heavy duty rear blades

- 16 forward & 16 reverse positions.
- Right or left offset.
- 5 tilt positions.
- 3 point linkage, cat. 1 & 2.
- ½" x 6" heat treated reversible cutting blade.
- ¼" moldboard thickness.
- Reinforced moldboard for increased strength.




MODEL	BRB-284	BRB-296
HP	30-80	30-80
in	84"	96"
lbs	524	561
lbs	602	644
	15° & 30°	15° & 30°
	up to 60°	up to 60°
in	up to 21"	up to 21"

### STANDARD




Front or rear tractor mounting



Up to 60° angling



Up to 21" offset



Up to 30° tilt

## OPTIONALS

# SOIL PULVERIZERS HD



• 2nd rear roller assembly  $\varnothing$  5  $\frac{5}{16}$ "

**009-9646** BPL-272

**009-9647** BPL-284

## OPTIONALS

# REAR BLADE SD

**BRB-001**

• Skid shoes



## OPTIONALS

# REAR BLADE HD

**BRB-001**

• Skid shoes



**BRB-002**

• Hydraulic offset control



## OPTIONALS

# LANDSCAPE RAKE BLR

**009-9159**

• Gauge wheels (standard duty series)



**BLR-002**

• Gauge wheels (subcompact series)

