

TILL-RITE T70

40-70 HP (30-52 KW)
540 rpm - cat. 1



Rotary tiller

Forward or reverse tilling rotation

- Highly engineered & rugged gearbox.
- Adjustable side skids for working depth control.
- Heavy duty shielded PTO shaft with slip clutch safety (1 3/8" ASAE cat. 6).
- Flanged rotor shaft for easy removal & service.
- Parking stand.
- 3 point linkage, cat. 1.
- Lateral ASA 100 chain drive transmission in oil bath.
- Standard six blades per flange for greater stability and finer soil pulverization.
- Outward turned blades keep the rotor supports clean and maximize working width.
- Heavy duty full size tiller blades.
- Wear protection on chain case.
- Max. working depth 8 3/4".



T70-382

										
HP	in	in	lbs	lbs	N°	N°	z	rpm	in	1 3/8"
40-70	82"	88"	879	1,009	10	60	12-14	221	8 3/4"	ASAE cat. 6 slip clutch



STANDARD



Forward or reverse tilling rotation



Gearbox manufactured by Befco



Lateral ASA 100 chain drive transmission in oil bath



Stamped steel rotor shaft supports and transmission



Rotor shaft with flanges for easy blade replacement

OPTIONALS TILL-RITE T60

RVRXXT60

• Reverse rotation (factory installed)



OPTIONALS TILL-RITE T70

RVRXXT70

• Reverse rotation (factory installed)



009-9855

• Areator rotor T70-382



OPTIONALS GREEN-RITE GRT

009-9875

• Gauge wheels for all models



• Front roller



009-9648

GRT-250

009-9516

GRT-258

009-9563

GRT-266

009-9566

GRT-282

Note: units may utilize gauge wheels or front roller for depth control, but not both

• Tiller rotor



009-9649

GRT-250

009-9517

GRT-258

009-9564

GRT-266

009-9567

GRT-282

• Rear roller scraper



009-9189

GRT-250

009-9190

GRT-258

009-9191

GRT-266

009-9192

GRT-282

• Cast iron roller rings
(factory installed)



CSR50GRT

GRT-250

CSR58GRT

GRT-258

CSR66GRT

GRT-266

CSR82GRT

GRT-282

• Seed conveyor kit



009-9139

GRT-250

009-9140

GRT-258

009-9141

GRT-266

009-9142

GRT-282