



TORNADO RHD

50-100 HP (37-74 KW)
540 rpm - cat. 1 & 2



cutting capacity

Heavy duty rotary cutters














- Cutting heights: from 2" to 8".
- Replaceable skids.
- Highly engineered & rugged gearbox.
- Heavy duty shielded PTO shaft with slip clutch safety (1 3/8" ASAE cat. 6).
- 3 point linkage, cat. 1 & 2.
- Floating top link.
- Front & rear protective chain shields standard.
- Exceptionally heavy duty 1/2"x4" spring steel blades.
- 3" cutting capacity.
- Laminated tail wheel with tapered roller bearings (5"x8"x15").
- Oval heavy duty stump jumper standard.
- Heavy duty reinforced deck.

WARNING:

Because of possible injury from thrown objects, all rotary cutters are potentially dangerous.

Any rotary cutter intended for use along roadways or other locations where people may be present must be used with safety shielding in place.

MODEL	RHD-472	RHD-484
 HP	50-100	60-100
 in	72"	84"
 in	76"	88"
 lbs	1,025	1,200
 lbs	1,025	1,200
 rpm	748	748
 fpm	13,878	16,191
 N°-in	2-1/2"x4"	2-1/2"x4"
 in	2"- 8"	2"- 8"
 N°-in	1-5"x8"x15"	1-5"x8"x15"
 1 3/8"	ASAE cat. 6 slip clutch	ASAE cat. 6 slip clutch



Heavy duty free swinging blades mounted on a high carbon steel rotor protected by an oval stump jumper

